Safety Data Sheet

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • Vacseal® Vacuum Leak Sealant With Brush, Original Formula

Clear

Synonyms • Vacseal® Vacuum Leak Sealant, Original

• 05049-AB; 05052-AB; 05053-AB; 05053GAL-AB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)• Temporary repairs for leaks in high vacuum and ultrahigh vacuum equipment to allow continued operation until "permanent" repairs can be scheduled.

1.3 Details of the supplier of the safety data sheet

• SPI Supplies Division Structure Probe, Inc.

206 Garfield Ave.

West Chester, PA 19380

United States http://www.2spi.com SDS@2spi.com

Telephone (General) • 1-(610)-436-5400

1.4 Emergency telephone number

Manufacturer• 1-(800)-424-9300 - Chemtrec **Manufacturer**• 1-(703)-741-5970 - Worldwide

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 2015/830]

2.1 Classification of the substance or mixture

CLP • Flammable Liquids 2 - H225

Aspiration 1 - H304 Skin Irritation 2 - H315 Eye Irritation 2 - H319

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Germ Cell Mutagenicity 2 - H341

Carcinogenicity 1B - H350

Specific Target Organ Toxicity Repeated Exposure 2 - H373 Hazardous to the aquatic environment Chronic 3 - H412

2.2 Label Elements

CLP

DANGER







Hazard statements • H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness H341 - Suspected of causing genetic defects.

H350 - May cause cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements

Prevention • P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P233 - Keep container tightly closed.

P235 - Keep cool.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mist, vapours and/or spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P281 - Use personal protective equipment as required.

Response •

P370+P378 - In case of fire: Use appropriate media for extinction.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 - Specific treatment, see supplemental first aid information.

P362 - Take off contaminated clothing and wash before reuse.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

P310 - Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

Storage/Disposal •

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P235 - Keep cool.

P405 - Store locked up.

P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

2.3 Other Hazards

CLP

According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

• Flammable Liquids 2

Aspiration 1 Skin Irritation 2 Eye Irritation 2

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Germ Cell Mutagenicity 2 Carcinogenicity 1A Reproductive Toxicity 1B

Specific Target Organ Toxicity Repeated Exposure 2

2.2 Label elements OSHA HCS 2012

DANGER







Hazard statements •

Highly flammable liquid and vapour

May be fatal if swallowed and enters airways

Causes skin irritation

Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Keep container tightly closed.

Keep cool.

Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist, vapours and/or spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • In case of fire: Use to extinguish.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

If on skin: Wash with plenty of water .

Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ŚWALLOWED: Immediately call a POISON CENTER/doctor . Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage/Disposal • Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or

Preparation Date: 10/October/2014 Revision Date: 20/December/2016 international regulations.

2.3 Other hazards OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Section 3 - Composition/Information on Ingredients

3.1 Substances

Material does not meet the criteria of a substance.

3.2 Mixtures

	Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments		
Ethylene, trichloro-	CAS:79-01-6 EC Number:201- 167-4 EU Index:602- 027-00-9	30% TO 60%	Skin-Rabbit LD50 • >20 g/kg Inhalation-Rat LC50 • 140700 mg/m³ 1 Hour(s) Ingestion/Oral-Rat LD50 • 4920 mg/kg	EU CLP: Annex VI, Table 3.1: Carc. 1B, H350; Muta. 2, H341; Eye Irrit. 2, H319; Skin Irrit. 2, H315; STOT SE 3: Narc., H336; Aquatic Chronic 3, H412 OSHA HCS 2012: Flam. Liq. 4; Carc. 1A; Muta. 2; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3: Narc.; Repr. 2; Asp. Tox. 1	NDA		
Xylene	CAS:1330-20-7 EC Number:215- 535-7 EU Index:601- 022-00-9	15% TO 30%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	EU CLP: Annex VI, Table 3.1: Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (InhI); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (InhI); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.	NDA		
Silicone Polymers	Proprietary	15% TO 25%	NDA	EU CLP: Not Classified OSHA HCS 2012: Not Classified	NDA		
Ethylbenzene	CAS:100-41-4 EC Number:202- 849-4 EU Index:601- 023-00-4	5% TO 15%	Ingestion/Oral-Rat LD50 • 3500 mg/kg Skin-Rabbit LD50 • 17800 μL/kg	EU CLP: Annex VI, Table 3.1: Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373 (Ears, Inhl); Asp. Tox. 1, H304 OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Inhl); Eye Irrit. 2; Carc. 2 (Inhl); Repr. 2 (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (Inhl); STOT RE 2 (Ear, Inhl); Asp. Tox. 1	NDA		

See Section 16 for full text of H-statements.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial
respiration if victim is not breathing. Do not use mouth-to-mouth method if victim
inhaled the substance; give artificial respiration with the aid of a pocket mask
equipped with a one-way valve or other proper respiratory medical device. Get medical
attention immediately.

Skin

 Wash skin with soap and water. Remove and isolate contaminated clothing. If irritation develops and persists, get medical attention.

Eye

 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

• Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention immediately if ingested.

4.2 Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media •

 Dry Chemical, CO2, water foam, "alcohol" foam, water spray to cool fire-exposed containers and disperse vapor.

Unsuitable Extinguishing Media

· Do not use a direct stream of water.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
 Containers may explode when heated.

Many liquids are lighter than water.

Vapors may form explosive mixtures with air.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products

· No data available

5.3 Advice for firefighters

• Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

LARGE FIRES: Cool containers with flooding quantities of water until well after fire is

out.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 CAUTION: Victim may be a source of contamination. Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE)

Emergency Procedures

• As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.
 Absorb or cover with dry earth, sand or other non-combustible material and transfer to

containers.

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.4 Reference to other sections

Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

 Use only in well ventilated areas. Keep away from heat, sparks, and flame. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapours and/or spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

 Store in a tightly closed container. Store in a cool, dry, well-ventilated place. Keep away from heat, sparks, and flame.

7.3 Specific end use(s)

 This item is not being offered for clinical or diagnostic applications, agricultural uses or for human or animal consumption. Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	NIOSH	OSHA		
Ethylbenzene	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA		
(100-41-4)	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established		
Xylene	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA		
(1330-20-7)	STELs	150 ppm STEL	Not established	Not established		
	Ceilings	Not established	Not established	200 ppm Ceiling		
Ethylene, trichloro- (79-01-6)	TWAs	10 ppm TWA	Not established	100 ppm TWA		
(. 5 5 . 5)	STELs	25 ppm STEL	Not established	Not established		

8.2 Exposure controls

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

 Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

· Wear chemical splash safety goggles.

Skin/Body

Environmental Exposure Controls

- Wear appropriate gloves. Wear long sleeves and/or protective coveralls.
- Controls should be engineered to prevent release to the environment, including
 procedures to prevent spills, atmospheric release and release to waterways. Follow
 best practice for site management and disposal of waste.
- An eyewash station and emergency shower must be available to the work station.

Additional Protection Measures

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Colorless to pale yellow liquid with solvent odor.
Color	Colorless to pale yellow.	Odor	Solvent odor.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	> 100 °C(> 212 °F)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	рН	Data lacking
Specific Gravity/Relative Density	= 1.01 @ 25 °C(77 °F) Water=1 (Trichloroethylene)	Water Solubility	Data lacking
Viscosity	105 Centistoke (cSt, cS) or mm2/sec	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility	-	•	-
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
Flammability		•	-
Flash Point	62 °F(16.6667 °C) PMCC (Pensky- Martins Closed Cup)	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental		•	-
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

· No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

· No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

· Hazardous polymerization will not occur.

10.4 Conditions to avoid

· Keep away from heat, sparks and flame.

10.5 Incompatible materials

· Oxidizing material can cause a reaction.

10.6 Hazardous decomposition products

· Carbon oxides and traces of incompletely burned carbon compounds.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

	Components						
Ethylene, trichloro- (30% TO 60%)	79- 01-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4920 mg/kg; Inhalation-Rat LC50 • 140700 mg/m³ 1 Hour(s); Skin-Rabbit LD50 • >20 g/kg; Irritation: Eye-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Skin-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Mouse TDLo • 22.4 mg/kg 32 Week(s)-Continuous; Liver:Hepatitis (hepatocellular necrosis), diffuse; Skin and Appendages:After systemic exposure:Dermatitis, other; Immunological Including Allergic:Autoimmune; Inhalation-Mouse TCLo • 500 ppm 4 Week(s)-Intermittent; Liver:Hepatitis (hepatocellular necrosis), zonal; Endocrine:Other changes; Immunological Including Allergic:Decrease in humoral immune response; Inhalation-Rat TCLo • 500 ppm 182 Day(s)-Intermittent; Kidney, Ureter, and Bladder:Interstitial nephritis; Kidney, Ureter, and Bladder:Renal function tests depressed; Mutagen: Sperm Morphology • Inhalation-Mouse • 100 ppm; Reproductive: Ingestion/Oral-Rat TDLo • 1140 mg/kg (14D pre-21D post); Reproductive Effects:Specific Developmental Abnormalities:Central nervous system; Ingestion/Oral-Rat TDLo • 76 mg/kg (multigenerations); Reproductive Effects:Specific Developmental Abnormalities:Urogenital system; Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain); Tumorigen / Carcinogen: Inhalation-Rat TCLo • 150 ppm 7 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Skin and Appendages:Other:Tumors					
Xylene (15% TO 30%)	1330 -20- 7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; Liver:Other changes; Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Man LCLo • 10000 ppm 6 Hour(s); Behavioral:General anesthetic; Lungs, Thorax, or Respiration:Cyanosis; Blood:Other changes; Inhalation-Human TCLo • 200 ppm; Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Other changes; Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Rabbit TCLo • 1 g/m³ 24 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s)(1-21D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue); Inhalation-Rat TDLo • 200 ppm 6 Hour(s)(4-20D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Effects on Newborn:Behavioral					
Ethylbenzene (5% TO 15%)	100- 41-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3500 mg/kg; Inhalation-Guinea Pig LCLo • 2500 ppm 8 Hour(s); Behavioral:Coma; Inhalation-Human TCLo • 21700 mg/m³; Behavioral:Antipsychotic; Inhalation-Mouse TCLo • 600 ppm 6 Minute(s); Lungs, Thorax, or Respiration:Respiratory depression; Skin-Rabbit LD50 • 17800 μL/kg; Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 15 mg 24 Hour(s)-Open • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 550 ppm 8 Hour(s) 5 Day(s)-Intermittent; Sense Organs and Special Senses:Ear:Change in acuity; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function; Mutagen: Specific locus test • Intraperitoneal-Mouse • 754 μmol/L; Micronucleus test • Unreported Route-Hamster • Embryo (Somatic cell) • 25 mg/L; Sister chromatid exchange • Unreported Route-Human • Lymphocyte (Somatic cell) • 10 mmol/L; Mutation in Mammalian Somatic Cells • Unreported Route-Mouse • Lymphocyte (Somatic cell) • 80 mg/L; Reproductive: Inhalation-Rabbit TCLo • 1 g/m³ 24 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 96 ppm 7 Hour(s)(1-19D preg); Reproductive Effects:Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Inhalation-Rat TCLo • 600 mg/m³ 24 Hour(s)(7-15D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on					

Embryo or Fetus:Fetal death; Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system;

Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent;

Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma;

Liver:Tumors; Inhalation-Rat TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS

criteria; Kidney, Ureter, and Bladder:Tumors; Inhalation-Rat TCLo • 23400 mg/kg 104 Week(s)-Intermittent;

Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Kidney, Ureter, and Bladder:Kidney tumors;

Reproductive Effects: Tumorigenic Effects: Testicular tumors

GHS Properties	Classification		
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2		
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2		
Skin sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Respiratory sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking		
Aspiration Hazard	EU/CLP • Aspiration 1 OSHA HCS 2012 • Aspiration 1		
Carcinogenicity	EU/CLP • Carcinogenicity 1B; May cause cancer OSHA HCS 2012 • Carcinogenicity 1A		
Germ Cell Mutagenicity	EU/CLP • Germ Cell Mutagenicity 2 OSHA HCS 2012 • Germ Cell Mutagenicity 2		
Toxicity for Reproduction	EU/CLP • Data lacking OSHA HCS 2012 • Toxic to Reproduction 1B		
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation		
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2		

Potential Health Effects Inhalation

Acute (Immediate)

• May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

Exposure to relatively low concentrations of ethylbenzene for several days to weeks
resulted in potentially irreversible damage to the inner ear and hearing of animals.

Skin

Acute (Immediate)

Causes skin irritation.

Chronic (Delayed)

Repeated exposure may cause skin dryness or cracking.

Eye

Acute (Immediate)

Causes serious eye irritation.

Chronic (Delayed)

No data available

Ingestion

Acute (Immediate)

Material may be aspirated into lungs during ingestion and/or subsequent vomiting.

Aspiration of this material will cause severe lung injury, chemical pneumonitis,

pulmonary edema or death.

Chronic (Delayed)

Mutagenic Effects Carcinogenic Effects No data available

Repeated and prolonged exposure may cause mutagenic effects.

· Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects						
CAS IARC NTP						
Ethylene, trichloro-	79-01-6	Group 1-Carcinogenic	Reasonably Anticipated to be Human Carcinogen			
Ethylbenzene	100-41-4	Group 2B-Possible Carcinogen	Not Listed			

Reproductive Effects

Repeated and prolonged exposure may cause reproductive effects.

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information

12.1 Toxicity

	CAS	
Vacseal® Vacuum Leak Sealant With Brush, Original Formula Clear	NDA	Aquatic Toxicity-Fish: 4 Day(s) LC50 16 mg/L Comments: Ethylene, trichloro- (79-01-6) 14 Day(s) NOEC 3.1 mg/L Comments: Ethylene, trichloro- (79-01-6) Aquatic Toxicity-Algae and Other Aquatic Plant(s): 3 Day(s) EC50 Green Algae 35.1-38.2 mg/L Comments: Ethylene, trichloro- (79-01-6)

· Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

· Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Preparation Date: 10/October/2014 Revision Date: 20/December/2016

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1866	Resin Solution, flammable	3	II	NDA
IMO/IMDG	UN1866	Resin Solution, flammable	3	II	NDA
IATA/ICAO	UN1866	Resin Solution, flammable	3	II	NDA

14.6 Special precautions for • None specified. user

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code · Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Ethylbenzene	100-41-4	Yes	No	Yes	No	Yes
Ethylene, trichloro-	79-01-6	Yes	No	Yes	No	Yes
Xylene	1330-20-7	Yes	No	Yes	No	Yes

Canada

_abor Canada - WHMIS 1988 - Classifications of Substances		
• Ethylbenzene	100-41-4	B2, D2A, D2B
• Xylene	1330-20-7	B2, D2A, D2B
• Ethylene, trichloro-	79-01-6	D1B, D2A, D2B
Canada - WHMIS 1988 - Ingredient Disclosure List		
• Ethylbenzene	100-41-4	0.1 %
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	1 %

Canada - CEPA - Priority Substances List		
Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Priority Substance List 1 (substance not considered toxic)
Ethylene, trichloro-	79-01-6	Priority Substance List 1 (substance considered toxic)

United States

Environment

Labor U.S OSHA - Process Safety Management - Highly Hazardous Chemicals			
• Ethylbenzene	100-41-4	Not Listed	

• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	Not Listed
J.S OSHA - Specifically Regulated Chemicals		
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	Not Listed
Environment		
U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants	100 11 1	
• Ethylbenzene	100-41-4	(listed under Ethyl benzene
• Xylene	1330-20-7	(isomers and mixtures)
Ethylene, trichloro-	79-01-6	
J.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities	s	4000 5 100 4541 5
• Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg fina RQ
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg fina RQ
• Ethylene, trichloro-	79-01-6	100 lb final RQ; 45.4 kg fina RQ
J.S CERCLA/SARA - Radionuclides and Their Reportable Quantities		
Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Ethylene, trichloro-	79-01-6	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA R	RQs	
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	Not Listed
J.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	Not Listed
J.S CERCLA/SARA - Section 313 - Emission Reporting		
Ethylbenzene	100-41-4	0.1 % de minimis concentration
• Xylene	1330-20-7	1.0 % de minimis concentration
Ethylene, trichloro-	79-01-6	0.1 % de minimis concentration
J.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
	79-01-6	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List]
Ethylbenzene	100-41-4	carcinogen, 6/11/2004	
• Xylene	1330-20-7	Not Listed	

• Ethylene, trichloro-	79-01-6	carcinogen, 4/1/1988
U.S California - Proposition 65 - Developmental Toxicity		
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	developmental toxicity, 1/31/2014
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	Not Listed
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)		
Ethylbenzene	100-41-4	54 μg/day NSRL (inhalation); 41 μg/day NSRL (oral)
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	14 μg/day NSRL (oral); 50 μg/day NSRL (inhalation)
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Ethylene, trichloro-	79-01-6	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
Ethylene, trichloro-	79-01-6	male reproductive toxicity, 1/31/14

15.2 Chemical Safety Assessment

· No Chemical Safety Assessment has been carried out.

15.3 Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

Relevant Phrases (code & full text)

 H226 - Flammable liquid and vapour H312 - Harmful in contact with skin

H332 - Harmful if inhaled

Revision Date

20/December/2016

Preparation Date

• 10/October/2014

Disclaimer/Statement of Liability

Caution! Do not use SPI Supplies products or materials in applications involving implantation within the body; direct or indirect contact with the blood pathway; contact with bone, tissue, tissue fluid, or blood; or prolonged contact with mucous membranes. Products offered by SPI Supplies are not designed or manufactured for use in implantation in the human body or in contact with internal body fluids or tissues. SPI Supplies will not provide to customers making devices for such applications any notice, certification, or information necessary for such medical device use required by US FDA (Food and Drug Administration) regulation or any other statute. SPI Supplies and Structure Probe, Inc. make no representation, promise,

express warranty or implied warranty concerning the suitability of these materials for use in implantation in the human body or in contact with internal body tissues of fluids. The information and recommendations set forth above are taken from sources believed to be accurate as of the date hereof, however SPI Supplies and Structure Probe, Inc. make no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assume no liability to any user thereof. The information contained in this sheet does not constitute a hazard assessment and should not be used in place of the user's own assessment of work place risks as required by other health and safety legislation. Be aware of the Structure Probe, Inc. Copyright Policy. Structure Probe, Inc. grants a nonexclusive license to make unlimited copies of this safety sheet for internal use only. Quite obviously, this information would pertain only to this material when purchased from SPI Supplies as product from other sources, with other ingredients and impurity levels could have substantially different properties.

Key to abbreviations NDA = No Data Available